







THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO CW INDUSTRIES INCORPORATED AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN CW INDUSTRIES PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM CW INDUSTRIES INCORPORATED, SOUTHAMPTON, PENNSYLVANIA USA.

Rating	3A. 125V , 1. 5A 250V AC	
Contact Resistance	50m ohm max.	
Insulation Resistance	DC 500V 100M ohm min.	
Dielectric Strength	AC 1000V 1 minute	




Cut-Out 3 mm thk. max

Frames are nylon (UL flame: 94V-2).  
Terminals are silver plated brass.



**FUNCTION**



**TERMINAL**

03	□	.110" SQ
05	□	SO

( ) = Momentary Function

RoHS Compliant

 <b>CW INDUSTRIES</b> Southampton, Pa. 18966 Tel 215.355.7080/www.cwind.com	Date Drawn: 2/09/11	Rev. 0	Unit: mm	Checked By: G.GULD
	Title: <b>PUSH BUTTON SWITCH</b>		CW P/N: <b>GPB510XSERIES</b>	